



T8 Ballasts - High Performance



PREMIUM QUALITY LIGHTING
800.323.8107 • 805.579.8279
www.pqlighting.com

- **UL Listed**
- **Sound Rating - Class A**
- **Min. Starting Temperature - 0 F**
- **Meets FCC Part 18C, Class A**
- **Outdoor Type 1**
- **No PCB's**
- **Crest Factor - Less than 1.70**
- **Power Factor (P.F) -> 0.98**
- **Input Frequency - 60 Hz**



Electronic Ballast Specifications

CODE #	BALLAST	LAMPS		INPUT (WITH 32WT8)				BALLAST	DIMENSIONS			
	MODELS	TYPE	QTY	VOLTAGE	POWER	P.F	THD(MAX)	FACTOR	L	W	H	MTG CENTER
70209	1/32IS-120	F32 T8	1	120V	28W	>0.98	20%	0.88nom	9.50"	1.65"	1.18"	8.91"
70200	1/32IS-277	F32 T8	1	277V	28W	>0.98	20%	0.88nom	9.50"	1.65"	1.18"	8.91"
70209	2/32IS-120	F32 T8	2	120V	55W	>0.98	20%	0.88nom	9.50"	1.65"	1.18"	8.91"
70200	2/32IS-277	F32 T8	2	277V	55W	>0.98	20%	0.88nom	9.50"	1.65"	1.18"	8.91"
70212	3/32IS-120	F32 T8	3	120V	84W	>0.99	10%	0.88nom	9.50"	1.65"	1.18"	8.91"
70203	3/32IS-277	F32 T8	3	277V	84W	>0.99	10%	0.88nom	9.50"	1.65"	1.18"	8.91"
70212	4/32IS-120	F32 T8	4	120V	110W	>0.99	10%	0.88nom	9.50"	1.65"	1.18"	8.91"
70203	4/32IS-277	F32 T8	4	277V	110W	>0.99	10%	0.88nom	9.50"	1.65"	1.18"	8.91"
70215	2/59IS-120	F96/T8/59W	2	120V	110W	>0.99	<10%	>0.88nom	9.50"	1.63"	1.13"	8.91"
70206	2/59IS-277	F96/T8/59W	2	277V	110W	>0.99	<10%	>0.88nom	9.50"	1.63"	1.13"	8.91"
70201	2/32IS-120/277	F32 T8	1/2	120/277V	1=27/28W, 2=55/54W	>0.98	20%	>0.87nom	9.50"	1.65"	1.18"	8.91"
70204	4/32IS-120/277	F32 T8	3/4	120/277V	3=84/83W, 4=109/107W	>0.99	10%	>0.88nom/>0.87nom	9.50"	1.65"	1.18"	8.91"
70205	3/32IS-120	F17 F25 F28 F32 T8	3/4	120V	84/109W	>0.99	10%	0.88nom	9.50"	1.65"	1.18"	8.91"