

T2 MINI-SPIRAL COMPACT FLUORESCENT



FEATURES & BENEFITS

With a mini-sized svelte tube design, Superior Life® T2 Mini-Spiral lamps can fit into a wider range of lighting fixtures, traditionally reserved for smaller lamps.

Consuming up to 75% less energy than incandescent lighting, T2 mini-spirals significantly reduce operating costs while providing high lumen output and excellent lumen maintenance.

- User Life over 10,000 Hours
- Input Line Voltage: 120VAC
- Input line Frequency: 50/60HZ
- Min. Starting Temp: -20°F
- Color Rendering Index: 82
- Electronic Ballast

Modified Rapid Start Technology

Lamp life performance is enhanced in applications where lamps are frequently switched on and off.

End-of-Life Protection

Our Superior Life® T2 mini-spirals have built in End-of-Life Protection Circuitry to protect the lamps from overheating at the end their life. CFLs without this technology can potentially overheat to the point where the plastics containing the ballast begin to melt causing health and fire hazards.



PART #	DESCRIPTION	WATT	VOLT	COLOR	MOL	LUMENS	CASE	INCANDESCENT EQUIVALENT:
80306	9WT2 MINI-SPIRAL/ENERGY STAR®	9	120	2700K	3.25	500	60	40
80317	9WT2 MINI-SPIRAL/SOFT WHITE	9	120	3500K	3.25	500	60	40
80309	9WT2 MINI-SPIRAL/SKY-BRITE®	9	120	5000K	3.25	500	60	40
80304	13WT2 MINI-SPIRAL/ENERGY STAR®	13	120	2700K	3.70	840	60	60
80314	13WT2 MINI-SPIRAL/SOFT WHITE	13	120	3500K	3.70	840	60	60
80334	13WT2 MINI-SPIRAL/DAY-BRITE™	13	120	4100K	3.70	840	60	60
80305	13WT2 MINI-SPIRAL/SKY-BRITE®	13	120	5000K	3.70	840	60	60
80307	18WT2 MINI-SPIRAL/ENERGY STAR®	18	120	2700K	4.20	1280	60	75
80332	18WT2 MINI-SPIRAL/SOFT WHITE	18	120	3500K	4.20	1280	60	75
80308	18WT2 MINI-SPIRAL/SKY-BRITE®	18	120	5000K	4.20	1280	60	75
80310	23WT2 MINI-SPIRAL/ENERGY STAR®	23	120	2700K	4.50	1600	60	100
80313	23WT2 MINI-SPIRAL/SOFT WHITE	23	120	3500K	4.50	1600	60	100
80316	23WT2 MINI-SPIRAL/DAY-BRITE™	23	120	4100K	4.50	1600	60	100
80311	23WT2 MINI-SPIRAL/SKY-BRITE®	23	120	5000K	4.50	1600	60	100
80346	26WT2 MINI-SPIRAL/ENERGY STAR®	26	120	2700K	4.96	1750	60	120
80349	26WT2 MINI-SPIRAL/SKY-BRITE®	26	120	5000K	4.96	1750	60	120



PREMIUM QUALITY LIGHTING
1.800.323.8107 • FAX: 1.877.619.7053
www.pqlighting.com

©2010 PQL, Inc.