

**SAVE UP TO 70%
ENERGY WITH COMPARABLE
LIGHT OUTPUT**

CFL-PAR



FEATURES & BENEFITS

- Available in 15W and 19W (PAR30) and 23W (PAR38)
- 60° Floodlight Reflector
- Wide Range of Operation Temperatures: 0°F - 120°F
- Optimal Light Output in Any Position
- Electronic Ballast with End-of-Life Protection*
- Use Indoor or Outdoor
- Suitable for Wet Applications
- 95% Lumen Maintenance

*** End-of-Life Protection:**

Our CFL-PARs have built in End-of-Life Protection Circuitry to protect the lamps from overheating at the end their life. CFLs without this technology can potentially overheat to the point where the plastics containing the ballast begin to melt causing health and fire hazards.

THREE COLOR OPTIONS:

WARM TONE 2850K	DAY-BRITE™ 4100K	SKY-BRITE® FULL SPECTRUM
---------------------------	----------------------------	------------------------------------



PART #	DESCRIPTION	WATTS	M.O.L.	COLOR	CRI	LUMENS	CASE
91673	15WPAR30/30K- SUPERIOR LIFE® ES	15	4.87	3000K	>82	750	12
91674	15WPAR30/SKY-BRITE®	15	4.87	5000K	>82	750	12
91672	15WPAR30/DAY-BRITE™	15	4.87	4100K	>82	750	12
91675	23WPAR38/30K- SUPERIOR LIFE® ES	23	5.00	3000K	>82	1350	12
91677	23WPAR38/DAY-BRITE™	23	5.00	4100K	>82	1200	12
91676	23WPAR38/SKY-BRITE®	23	5.00	5000K	>82	1350	12

INCANDESCENT OR HALOGEN EQUIVALENT:
60W
60W
60W
75W
75W
75W



This lamp contains mercury. For proper lamp disposal, contact your local municipal solid waste agency directly, call 888-537-4874 or visit lamprecycle.org for state-specific lamp recycling options.



PREMIUM QUALITY LIGHTING
1.800.323.8107 • FAX: 1.877.619.7053
www.pqlighting.com

©2011 PQL, Inc.