



# LED HIGH WATTAGE

## 360° LIGHTING

The Superior Life® LED high wattage lamp is a convenient and easy-to-install LED solution for acorn, globe and bollard fixtures. The LED lamp delivers a high lumen output with a 360-degree optical design that provides even light distribution. They consume up to 80% less energy, thereby significantly reducing operating costs. The superior life hours of this lamp make it ideal for hard to reach places, reducing maintenance.

- **BRIGHT AND CONSISTENT**  
Glare-free that ensures clean whites and bright colors.
- **REDUCED HEAT OUTPUT**
- **NO DELAY, QUICK START UP**  
No Flickering or Humming
- **VIBRATION AND WATER RESISTANT**
- **ECO-FRIENDLY, MERCURY FREE**
- **COMPACT LIGHTWEIGHT DESIGN**
- **SIMPLE INSTALLATION**

ITEM#	DESCRIPTION	WATTS	CCT	LM	LM/W	BEAM	CRI	MOL	MOD	VOLTS	LIFE	TRAD. EQUIV.	CASE
90779	LED 12WT22/360°/CL/50K/MED 100-300V	12	50K	1300	108	360°	80	6.5"	2.8"	100-300	50K	40W	12
91122	LED 14WT22/320°/CL/50K/MED/120-277V/V4 - SL®	14	50K	1500	107	320°	80	5.7"	2.8"	120-277	50K	45W	24
91575	LED 16WT19/360°/CL/50K/MED/120-277V/V5 - SL®	16	50K	2080	130	360°	80	6.5"	2.4"	120-277	50K	50W	12
90781	LED 16WT22/360°/STREET LIGHT/50K/MED-100-300V	16	50K	1750	109	360°	80	6.9"	2.8"	100-300	50K	50W	12
91576	LED 22WT19/360°/CL/50K/MED/120-277V/V5 - SL®	22	50K	2860	130	360°	80	7.1"	2.4"	120-277	50K	60W	12
91577	LED 27WT30/360°/CL/50K/MED/120-277V/V5 - SL®	27	50K	3510	130	360°	80	7.3"	3.7"	120-277	50K	120W	12
91578	LED 36WT30/360°/CL/50K/MED/120-277V/V5 - SL®	36	50K	4680	130	360°	80	8.3"	3.7"	120-277	50K	150W	12
91130	LED 45WT29/320°/CL/50K/MED/120-277V/V4 - SL®	45	50K	4700	104	320°	80	10.4"	3.7"	120-277	50K	150W	12
91579	LED 45WT30/360°/CL/50K/MED/120-277V/V5 - SL®	45	50K	5850	130	360°	80	9.3"	3.7"	120-277	50K	150W	12
91580	LED 45WT30/360°/CL/50K/MOG/120-277V/V5 - SL® DLC	45	50K	5850	130	360°	82	9.3"	3.7"	120-277	50K	150W	12
91132	LED 46WT29/320°/CL/50K/MOG/120-277V/V4 - SL® DLC	46	50K	4474	97	320°	82	10.4"	3.7"	120-277	50K	150W	12
91135	LED 52WT29/320°/CL/50K/MOG/120-277V/V4 - SL® DLC	52	50K	4852	93	320°	84	10.4"	3.7"	120-277	50K	180W	12
91581	LED 54WT30/360°/CL/50K/MOG/120-277V/V5 - SL® DLC	54	50K	7020	130	360°	82	10.2"	3.7"	120-277	50K	200W	12
91585	LED 65WT30/360°/CL/50K/MOG/120-277V/V5 - SL®	65	50K	8450	130	360°	82	12"	3.7"	120-277	50K	200W	12
91582	LED 75WT30/360°/CL/50K/MOG/120-277V/V5 - SL® DLC	75	50K	9750	130	360°	82	12"	3.7"	120-277	50K	200W	12
91137	LED 80WT40/320°/CL/50K/MOG/120-277V/V4 - SL® DLC	80	50K	7675	96	320°	84	10.9"	5.7"	120-277	50K	200W	4
91583	LED 100WT44/360°/CL/50K/MOG/120-277V/V5 - SL® DLC	100	50K	13000	130	360°	82	9.6"	5.5"	120-277	50K	400W	6
91584	LED 120WT44/360°/CL/50K/MOG/120-277V/V5 - SL® DLC	120	50K	15600	130	360°	82	10.4"	5.5"	120-277	50K	400W	6
91590	LED 120W HIGH BAY RETROFIT/CL/50K/MOG/120-277V - SL® DLC	120	50K	18000	150	360°	80	8.8"	7.9"	120-277	50K	400W	6
<b>ACCESSORIES</b>													
82234	E39 (MOGUL) TO E26 (MEDIUM) LAMPHOLDER REDUCE												10
82235	E26 (MEDIUM) TO E39 (MOGUL) LAMPHOLDER ENLARGER												10

Key: SL = Superior Life® / LM = Lumens / TRAD. EQUIV. = Traditional Equivalent

NOTE: Due to multiple input voltage integrated circuits, these items are not compatible with dimming devices.  
 • DLC items are certified at the time of production. Please visit [www.designlights.org](http://www.designlights.org) for the most recent list of qualified products. • Published lumens on LED products are approximate and may vary slightly.



PREMIUM QUALITY LIGHTING® • [www.PQLighting.com](http://www.PQLighting.com)

© 2018 P.Q.L., Inc. • 2285 Ward Avenue • Simi Valley, Ca 93065 • 800.323.8107 • Fax: 877.619.7053

GO GREEN



0818