



LED STADIUM LIGHTING

Superior Life® LED Stadium fixtures replace existing Metal Halide or HPS fixtures. They consume up to 80% less energy, significantly reducing operating costs and are environmentally friendly. The construction allows excellent heat dispersion and convenient installation.

- **BRIGHT AND CONSISTENT**
Uniform light distribution and high lumen output.
- **LONG LIFE (50,000 HRS)**
There is no need for frequent maintenance which make them ideal for hard to reach areas.
- **NO DELAY, QUICK START UP**
Instant-On, No Flickering or Humming
- **ECO-FRIENDLY, MERCURY FREE**
- **COMPACT DESIGN**
- **SIMPLE INSTALLATION**
- **ADJUSTABLE LIGHT ANGLE**
- **SURGE PROTECTION DEVICE**

These are only offered as SPECIAL ORDER (not stocked) and a minimum order quantity will apply. The lead-time is approx. 60 to 75 days.

ITEM#	DESCRIPTION	WATT	CCT	LM	LM/W	BEAM	CRI	VOLTS	TRAD. EQUIV.	CASE
84100	LED 300W STADIUM/50K/30°/120-277V/TRUNNION - SL°	300	50K	39000	130	30°	70	120-277	1000W	1
84101	LED 400W STADIUM/50K/30°/120-277V/TRUNNION - SL°	400	50K	52000	130	30°	70	120-277	1500W	1
84102	LED 500W STADIUM/50K/30°/120-277V/TRUNNION - SL°	500	50K	65000	130	30°	70	120-277	1500W+	1
84103	LED 600W STADIUM/50K/40°/120-277V/TRUNNION - SL°	600	50K	76816	126	40°	83	120-277	1500W+	1
84104	LED 750W STADIUM/50K/40°/120-277V/TRUNNION - SL°	750	50K	95608	126	40°	83	120-277	1500W+	1
84105	LED 1000W STADIUM/50K/40°/120-277V/TRUNNION - SL°	1000	50K	127808	124	40°	83	120-277	1500W+	1
84106	LED 1250W STADIUM/50K/40°/120-277V/TRUNNION - SL°	1250	50K	156000	125	40°	70	120-277	1500W+	1

Key: DIMM = Dimmable / SL = Superior Life® / LM = Lumens / TRAD. EQUIV. = Traditional Equivalent

NOTE: Published lumens on LED products are approximate and may vary slightly. - DLC items are certified at the time of production. Please visit www.designlights.org for the most recent list of qualified products.



PREMIUM QUALITY LIGHTING • www.PQLighting.com

© 2018 P.Q.L., Inc. • 2285 Ward Avenue • Simi Valley, Ca 93065 • 800.323.8107 • Fax: 877.619.7053

