



LED PANEL LIGHTING

The Superior Life® LED Panel Light with super bright SMD LEDs offers high luminous efficiency. They consume up to 80% less energy, significantly reducing operating costs and are environmentally friendly. The slim attractive design of our LED Panel Lights are perfect for offices, hotels, restaurants, schools, factories, galleries, retail, hospitals, airports and other architectural features.

- **BRIGHT AND CONSISTENT**

The unique construction of Superior Life® LED Panels offers uniform light distribution throughout the face creating an even glare-free illumination that ensures clean bright whites and vibrant colors.

- **NO DELAY, QUICK START UP**

No Flickering or Humming

- **REDUCED HEAT OUTPUT**

Our Superior Life® LED Panels remain cool to the touch, increasing placement possibilities and eliminating the need for ventilation.

- **ZERO MAINTENANCE**

- **VIBRATION AND WATER RESISTANT**

- **ECO-FRIENDLY, MERCURY FREE**

- **COMPACT LIGHTWEIGHT DESIGN**

- **SIMPLE INSTALLATION**

Hanging or mounting kits sold separately. Earthquake proof hooks included with V5 panels.



By incorporating advanced circuitry into our LED products, SUPERIOR LIFE® dimmable LED lamps function with switch dimmers just as normal incandescents do by allowing full linear dimming control.



NOTE: Items may not be compatible with all dimming devices. - DLC items are certified at the time of production. Please visit www.designlights.org for the most recent list of qualified products. - Published lumens on LED products are approximate and may vary slightly.



PREMIUM QUALITY LIGHTING • www.PQLighting.com

© 2018 PQL, Inc. • 2285 Ward Avenue • Simi Valley, Ca 93065 • 800.323.8107 • Fax: 877.619.7053



ITEM#	DESCRIPTION	WATT	CCT	LM	LM/W	BEAM	CRI	VOLTS	LIFE	TRAD. EQUIV.	CASE
PREMIUM PANELS											
55301	LED 2X2 PANEL 20W/40K/120-277V/DIMMABLE/V5 - SL° DLC	20	40K	2632	128	120°	83	120-277V	50K	50W	2
55302	LED 2X2 PANEL 20W/50K/120-277V/DIMMABLE/V5 - SL° DLC	20	50K	2650	130	120°	82	120-277V	50K	50W	2
55304	LED 2X2 PANEL 32W/40K/120-277V/DIMMABLE/V5 - SL° DLC	32	40K	4081	127	120°	83	120-277V	50K	100W	2
55305	LED 2X2 PANEL 32W/50K/120-277V/DIMMABLE/V5 - SL° DLC	32	50K	4111	129	120°	82	120-277V	50K	100W	2
55311	LED 2X4 PANEL 36W/50K/120-277V/DIMMABLE/V5 - SL° DLC	36	50K	4637	128	120°	83	120-277V	50K	150W	2
55313	LED 2X4 PANEL 50W/40K/120-277V/DIMMABLE/V5 - SL° DLC	50	40K	6243	129	120°	83	120-277V	50K	200W	2
STANDARD PANELS											
55170	LED 1X4 PANEL 35W/40K/120-277V/DIMMABLE/V4 - SL°	35	40K	3500	90	120°	83	120-277V	50K	75W	2
55284	LED 2X2 PANEL 40W/30K/120-277V/DIMMABLE/V5 - SL° DLC	40	30K	4027	101	120°	83	120-277V	50K	100W	2
55285	LED 2X2 PANEL 40W/40K/120-277V/DIMMABLE/V5 - SL° DLC	40	40K	4174	104	120°	83	120-277V	50K	100W	2
55286	LED 2X2 PANEL 40W/50K/120-277V/DIMMABLE/V5 - SL° DLC	40	50K	4322	106	120°	83	120-277V	50K	100W	2
55287	LED 2X4 PANEL 50W/30K/120-277V/DIMMABLE/V5 - SL° DLC	50	30K	5255	104	120°	83	120-277V	50K	150W	2
55288	LED 2X4 PANEL 50W/40K/120-277V/DIMMABLE/V5 - SL° DLC	50	40K	5311	105	120°	83	120-277V	50K	150W	2
55289	LED 2X4 PANEL 50W/50K/120-277V/DIMMABLE/V5 - SL° DLC	50	50K	5368	107	120°	83	120-277V	50K	150W	2
55290	LED 2X4 PANEL 75W/30K/120-277V/DIMMABLE/V5 - SL° DLC	75	30K	7426	99	120°	83	120-277V	50K	200W	2
55291	LED 2X4 PANEL 75W/40K/120-277V/DIMMABLE/V5 - SL° DLC	75	40K	7659	101	120°	83	120-277V	50K	200W	2
55292	LED 2X4 PANEL 75W/50K/120-277V/DIMMABLE/V5 - SL° DLC	75	50K	7882	103	120°	83	120-277V	50K	200W	2
55182	LED 2X4 PANEL 75W/40K/120-277V/DIMMABLE/V4 - SL°	75	40K	7500	95	120°	83	120-277V	50K	200W	2
ACCESSORIES											
55294*	2x2 SURFACE MOUNTED KIT FOR LED V5 PANEL/WHITE - SL°										10
55296	2x2 SUSPENDED CABLE MOUNTING KIT FOR LED PANEL - SL° (39.4" L x 0.06" DIA; 44 LB Pull Test)										1
55297	1x4 or 2x4 SUSPENDED CABLE MOUNTING KIT FOR LED PANEL - SL° (39.4" L x 0.06" DIA; 44 LB Pull Test)										1
55280	EMERGENCY PACK FOR LED FIXTURE 15W/90 MIN/V5 - SL°										10
55281	EMERGENCY PACK FOR LED FIXTURE 25W/90 MIN/V5 - SL°										10

*Surface Mount Kits are not compatible with the V4 LED Panels (551XX)

Key: DIMM = Dimmable / SL = Superior Life® / LM = Lumens / TRAD. EQUIV. = Traditional Equivalent

NOTE: Items may not be compatible with all dimming devices. - DLC items are certified at the time of production. Please visit www.designlights.org for the most recent list of qualified products. • Published lumens on LED products are approximate and may vary slightly.



PREMIUM QUALITY LIGHTING • www.PQLighting.com

© 2018 PQL, Inc. • 2285 Ward Avenue • Simi Valley, Ca 93065 • 800.323.8107 • Fax: 877.619.7053

GO GREEN

