



LED PANEL LIGHTING



The Superior Life® LED Panel Light with super bright SMD LEDs offers high luminous efficiency. They consume up to 80% less energy, significantly reducing operating costs and are environmentally friendly. The slim attractive design of our LED Panel Lights are perfect for offices, hotels, restaurants, schools, factories, galleries, retail, hospitals, airports and other architectural features.

• BRIGHT AND CONSISTENT

The unique construction of Superior Life® LED Panels offers uniform light distribution throughout the face creating an even glare-free illumination that ensures clean bright whites and vibrant colors.

• NO DELAY, QUICK START UP

No Flickering or Humming

• REDUCED HEAT OUTPUT

Our Superior Life® LED Panels remain cool to the touch, increasing placement possibilities and eliminating the need for ventilation.

• ZERO MAINTENANCE

• VIBRATION AND WATER RESISTANT

• ECO-FRIENDLY, MERCURY FREE

• COMPACT LIGHTWEIGHT DESIGN

• SIMPLE INSTALLATION

Hanging or mounting kits sold separately. Earthquake proof hooks included with V5 panels.



By incorporating advanced circuitry into our LED products, SUPERIOR LIFE® dimmable LED lamps function with switch dimmers just as normal incandescents do by allowing full linear dimming control.

| ITEM# | DESCRIPTION | WATT | CCT | LM | LM/W | BEAM | CRI | VOLTS | LIFE | TRAD. EQUIV. | CASE |
|------------------------|---|------|-----|------|------|------|-----|----------|------|--------------|------|
| PREMIUM PANELS | | | | | | | | | | | |
| 55301 | LED 2X2 PANEL 20W/40K/120-277V/DIMMABLE/V5 - SL® DLC | 20 | 40K | 2632 | 128 | 120° | 83 | 120-277V | 50K | 50W | 2 |
| 55304 | LED 2X2 PANEL 32W/40K/120-277V/DIMMABLE/V5 - SL® DLC | 32 | 40K | 4081 | 127 | 120° | 83 | 120-277V | 50K | 100W | 2 |
| STANDARD PANELS | | | | | | | | | | | |
| 55287 | LED 2X4 PANEL 50W/30K/120-277V/DIMMABLE/V5 - SL® DLC | 50 | 30K | 5255 | 104 | 120° | 83 | 120-277V | 50K | 150W | 2 |
| 55288 | LED 2X4 PANEL 50W/40K/120-277V/DIMMABLE/V5 - SL® DLC | 50 | 40K | 5311 | 105 | 120° | 83 | 120-277V | 50K | 150W | 2 |
| 55290 | LED 2X4 PANEL 75W/30K/120-277V/DIMMABLE/V5 - SL® DLC | 75 | 30K | 7426 | 99 | 120° | 83 | 120-277V | 50K | 200W | 2 |
| 55292 | LED 2X4 PANEL 75W/50K/120-277V/DIMMABLE/V5 - SL® DLC | 75 | 50K | 7882 | 103 | 120° | 83 | 120-277V | 50K | 200W | 2 |
| ACCESSORIES | | | | | | | | | | | |
| 55296 | 2x2 SUSPENDED CABLE MOUNTING KIT FOR LED PANEL - SL® (39.4" L x 0.06" DIA; 44 LB Pull Test) | | | | | | | | | | 1 |
| 55280 | EMERGENCY PACK FOR LED FIXTURE 15W/90 MIN/V5 - SL® | | | | | | | | | | 10 |
| 55281 | EMERGENCY PACK FOR LED FIXTURE 25W/90 MIN/V5 - SL® | | | | | | | | | | 10 |

*Surface Mount Kits are not compatible with the V4 LED Panels (551XX)

Key: DIMM = Dimmable / SL = Superior Life® / LM = Lumens / TRAD. EQUIV. = Traditional Equivalent

NOTE: Not all product variations listed on this page are DLC qualified. Visit www.designlights.org/search to confirm qualification. - Items may not be compatible with all dimming devices. - Published lumens on LED products are approximate and may vary slightly.

SUITABLE FOR
DAMP
LOCATIONS



PREMIUM QUALITY LIGHTING® • www.PQLighting.com

© 2018 P.Q.L., Inc. • 2285 Ward Avenue • Simi Valley, Ca 93065 • 800.323.8107 • Fax: 877.619.7053

GO GREEN



0918