



NEW FOR 2018

LED PANEL

LIGHTING

The Superior Life® LED Panel Light with super bright SMD LEDs offers high luminous efficiency. They consume up to 80% less energy, significantly reducing operating costs and are environmentally friendly. The slim attractive design of our LED Panel Lights are perfect for offices, hotels, restaurants, schools, factories, galleries, retail, hospitals, airports and other architectural features.

- **BRIGHT AND CONSISTENT**

The unique construction of Superior Life® LED Panels offers uniform light distribution throughout the face creating an even glare-free illumination that ensures clean bright whites and vibrant colors.

- **NO DELAY, QUICK START UP**

No Flickering or Humming

- **REDUCED HEAT OUTPUT**

Our Superior Life® LED Panels remain cool to the touch, increasing placement possibilities and eliminating the need for ventilation.

- **ZERO MAINTENANCE**

- **VIBRATION AND WATER RESISTANT**

- **ECO-FRIENDLY, MERCURY FREE**

- **COMPACT LIGHTWEIGHT DESIGN**

- **SIMPLE INSTALLATION**

Hanging or mounting kits sold separately.



By incorporating advanced circuitry into our LED products, SUPERIOR LIFE® dimmable LED lamps function with switch dimmers just as normal incandescents do by allowing full linear dimming control.



NOTE: Items may not be compatible with all dimming devices. - DLC items are certified at the time of production. Please visit www.designlights.org for the most recent list of qualified products. - Published lumens on LED products are approximate and may vary slightly.



PREMIUM QUALITY LIGHTING® • www.PQLighting.com

© 2018 P.Q.L., Inc. • 2285 Ward Avenue • Simi Valley, Ca 93065 • 800.323.8107 • Fax: 877.619.7053



0518

ITEM#	DESCRIPTION	WATT	CCT	LM	LM/W	BEAM	CRI	VOLTS	LIFE	TRAD. EQUIV.	CASE
PREMIUM PANELS											
55326	LED 2X2 PANEL 28W/35K/120-277V/DIMMABLE/V5 - SL®	28	35K	3500	125	120°	82	120-277V	50K	50W	2
55327	LED 2X2 PANEL 28W/40K/120-277V/DIMMABLE/V5 - SL® DLC	28	40K	3556	127	120°	82	120-277V	50K	50W	2
55328	LED 2X2 PANEL 28W/50K/120-277V/DIMMABLE/V5 - SL® DLC	28	50K	3612	129	120°	82	120-277V	50K	50W	2
55329	LED 2X2 PANEL 36W/35K/120-277V/DIMMABLE/V5 - SL®	36	35K	4500	125	120°	82	120-277V	50K	100W	2
55330	LED 2X2 PANEL 36W/40K/120-277V/DIMMABLE/V5 - SL® DLC	36	40K	4608	128	120°	82	120-277V	50K	100W	2
55331	LED 2X2 PANEL 36W/50K/120-277V/DIMMABLE/V5 - SL® DLC	36	50K	4644	129	120°	82	120-277V	50K	100W	2
55332	LED 2X4 PANEL 36W/35K/120-277V/DIMMABLE/V5 - SL®	36	35K	4464	124	120°	82	120-277V	50K	100W	2
55333	LED 2X4 PANEL 36W/40K/120-277V/DIMMABLE/V5 - SL® DLC	36	40K	4500	125	120°	82	120-277V	50K	100W	2
55334	LED 2X4 PANEL 36W/50K/120-277V/DIMMABLE/V5 - SL® DLC	36	50K	4536	126	120°	82	120-277V	50K	100W	2
55335	LED 2X4 PANEL 46W/35K/120-277V/DIMMABLE/V5 - SL®	46	35K	5796	126	120°	82	120-277V	50K	150W	2
55336	LED 2X4 PANEL 46W/40K/120-277V/DIMMABLE/V5 - SL® DLC	46	40K	5842	127	120°	82	120-277V	50K	150W	2
55337	LED 2X4 PANEL 46W/50K/120-277V/DIMMABLE/V5 - SL® DLC	46	50K	5934	129	120°	82	120-277V	50K	150W	2
STANDARD PANELS											
55338	LED 1X4 PANEL 40W/35K/120-277V/DIMMABLE/V5 - SL®	40	35K	4200	105	120°	82	120-277V	50K	75W	2
55339	LED 1X4 PANEL 40W/40K/120-277V/DIMMABLE/V5 - SL® DLC	40	40K	4320	108	120°	82	120-277V	50K	75W	2
55340	LED 1x4 PANEL 40W/50K/120-277V/DIMMABLE/V5 - SL® DLC	40	50K	4360	109	120°	82	120-277V	50K	75W	2
55341	LED 2X2 PANEL 40W/35K/120-277V/DIMMABLE/V5 - SL® DLC	40	35K	4200	105	120°	80	120-277V	50K	75W	2
55342	LED 2X2 PANEL 40W/40K/120-277V/DIMMABLE/V5 - SL® DLC	40	40K	4320	108	120°	80	120-277V	50K	75W	2
55343	LED 2X2 PANEL 40W/50K/120-277V/DIMMABLE/V5 - SL® DLC	40	50K	4360	109	120°	80	120-277V	50K	75W	2
55344	LED 2X4 PANEL 50W/35K/120-277V/DIMMABLE/V5 - SL® DLC	50	35K	5150	103	120°	80	120-277V	50K	150W	2
55345	LED 2X4 PANEL 50W/40K/120-277V/DIMMABLE/V5 - SL® DLC	50	40K	5200	104	120°	80	120-277V	50K	150W	2
55346	LED 2X4 PANEL 50W/50K/120-277V/DIMMABLE/V5 - SL® DLC	50	50K	5350	107	120°	80	120-277V	50K	150W	2
55347	LED 2X4 PANEL 65W/35K/120-277V/DIMMABLE/V5 - SL® DLC	65	35K	6500	100	120°	80	120-277V	50K	200W	2
55348	LED 2X4 PANEL 65W/40K/120-277V/DIMMABLE/V5 - SL® DLC	65	40K	6630	102	120°	80	120-277V	50K	200W	2
55349	LED 2X4 PANEL 65W/50K/120-277V/DIMMABLE/V5 - SL® DLC	65	50K	6760	104	120°	80	120-277V	50K	200W	2
ACCESSORIES											
55127	1X4 FLANGE KIT FOR PANEL & TROFFER/WHITE - SL®										1
55128	2X2 FLANGE KIT FOR PANEL & TROFFER/WHITE - SL®										1
55129	2X4 FLANGE KIT FOR PANEL & TROFFER/WHITE - SL®										1
55317	1x4 SURFACE MOUNTED KIT FOR LED PANEL/WHITE - SL®										1
55323	2X2 SURFACE MOUNTED KIT FOR LED PANEL/WHITE - SL®										1
55325	2X4 SURFACE MOUNTED KIT FOR LED PANEL/WHITE - SL®										1
55322	1X4 SUSPENDED CABLE MOUNTING KIT FOR LED PANEL - SL®										1
55324	2X2 or 2X4 SUSPENDED CABLE MOUNTING KIT FOR LED PANEL - SL®										1
55319	EMERGENCY PACK FOR LED FIXTURE 8W/90 MIN (Requires Mounting Bracket)										1
55320	EMERGENCY PACK FOR LED FIXTURE 16W/90 MIN (Requires Mounting Bracket)										1
55321	EMERGENCY PACK FOR LED FIXTURE 25W/90 MIN (Requires Mounting Bracket)										1
55356	MOUNTING BRACKET FOR EMERGENCY BATTERY FOR 1X4 LED PANEL										1
55357	MOUNTING BRACKET FOR EMERGENCY BATTERY FOR 2X2 OR 2X4 LED PANEL										1

Key: DIMM = Dimmable / SL = Superior Life® / LM = Lumens / TRAD. EQUIV. = Traditional Equivalent

NOTE: Items may not be compatible with all dimming devices. - DLC items are certified at the time of production. Please visit www.designlights.org for the most recent list of qualified products. - Published lumens on LED products are approximate and may vary slightly.



PREMIUM QUALITY LIGHTING® • www.PQLighting.com

© 2018 P.Q.L., Inc. • 2285 Ward Avenue • Simi Valley, Ca 93065 • 800.323.8107 • Fax: 877.619.7053

GO GREEN

