



LED RETROFIT CAN

The Superior Life® LED Retrofit Cans are replacements for existing, less efficient incandescent and compact fluorescent (CFL) light sources. They consume up to 80% less energy, thereby significantly reducing operating costs. The superior life hours of this lamp make it ideal for hard to reach places, reducing maintenance.

ECO-FRIENDLY, MERCURY FREE • NO UV • NO PROJECTED HEAT

**Dimmable
LED**

By incorporating advanced circuitry into our LED products, SUPERIOR LIFE® dimmable LED lamps function with switch dimmers just as normal incandescents do by allowing full linear dimming control.



Note: For covered ceilings only. Items may not be compatible with all dimming devices. • Energy Star® items are certified at the time of production. Please visit www.energystar.gov for the most recent list of qualified products. • Published lumens on LED products are approximate and may vary slightly.



PREMIUM QUALITY LIGHTING • www.PQLighting.com

© 2018 PQL, Inc. • 2285 Ward Avenue • Simi Valley, Ca 93065 • 800.323.8107 • Fax: 877.619.7053



ITEM#	DESCRIPTION	WATT	DIMM	CCT	LM	LM/W	BEAM	CRI	MOL	VOLT	BASE	LIFE	TRAD. EQUIV.	CASE
RETROFIT CANS														
90906	LED RETROFIT 4" CAN 9W/50K/MED/DIMM - SL° ES	9	YES	50K	680	76	90°	82	3.2	120V	MEDIUM	50K	60W	12
90910	LED RETROFIT 4" CAN 10W/30K/MED/DIMM V4 - SL° ES	10	YES	30K	700	70	95°	83	2.8	120V	MEDIUM	50K	60W	12
90919	LED RETROFIT 4" SQ CAN 10W/30K/MED/DIMM V4 - SL° ES	10	YES	30K	610	61	100°	83	2.8	120V	MEDIUM	50K	60W	12
90925	LED RETROFIT 5"/6" CAN 10.5W/30K/MED/DIMM - SL° ES	10.5	YES	30K	760	72	95°	93	2.4	120V	MEDIUM	50K	60W	12
90916	LED RETROFIT 5"/6" CAN 10.5W/50K/MED/DIMM - SL°	10.5	YES	50K	760	72	95°	93	2.4	120V	MEDIUM	50K	60W	12
90915	LED RETROFIT 5"/6" CAN 12W/30K/MED/DIMM - SL° ES	12	YES	30K	840	70	100°	91	3.5	120V	MEDIUM	50K	75W	8
90922	LED RETROFIT 5"/6" CAN 15W/30K/MED/DIMM - SL° ES	15	YES	30K	1000	67	95°	93	2.4	120V	MEDIUM	50K	75W	12
90928	LED RETROFIT 5"/6" CAN 15W/50K/MED/DIMM - SL° ES	15	YES	50K	1000	67	95°	95	2.4	120V	MEDIUM	50K	75W	12
91003	LED RETROFIT 6" CAN 15W/30K/110-277V/DIMM* - SL° ES	15	@ 120V	30K	1000	67	95°	92	4.7	110-277V	--	50K	75W	12
91004	LED RETROFIT 6" CAN 15W/50K/110-277V/DIMM* - SL° ES	15	@ 120V	50K	1100	73	95°	93	4.7	110-277V	--	50K	75W	12
90992	LED RETROFIT 8" CAN 25W/30K/100-277V/DIMM* - SL° ES	25	**	30K	1950	78	95°	83	5.3	100-277V	--	50K	100W	6
90993	LED RETROFIT 8" CAN 25W/50K/100-277V/DIMM* - SL° ES	25	**	50K	1950	78	95°	83	5.3	100-277V	--	50K	100W	6
90994	LED RETROFIT 8" CAN 30W/30K/100-277V/DIMM* - SL° ES	30	**	30K	2350	78	95°	83	5.3	100-277V	--	50K	100W	6
90995	LED RETROFIT 8" CAN 30W/50K/100-277V/DIMM* - SL° ES	30	**	50K	2350	78	95°	83	5.3	100-277V	--	50K	100W	6
RETROFIT DISKS														
91013	LED RETROFIT 5"/6" DISK LIGHT 15W/30K/MED/DIMM - SL° ES	15	YES	30K	1100	63	105°	90	1.3	120V	--	50K	75W	12
91014	LED RETROFIT 5"/6" DISK LIGHT 15W/40K/MED/DIMM - SL° ES	15	YES	40K	1150	67	105°	90	1.3	120V	--	50K	75W	12
91015	LED RETROFIT 5"/6" DISK LIGHT 15W/50K/MED/DIMM - SL° ES	15	YES	50K	1200	70	105°	90	1.3	120V	--	50K	75W	12
ACCESSORY														
90905-QC	CONNECTOR FOR GU24 BASE ON 4" AND 5"/6" CAN													1

**9099X produced in 2016 thru 2017 are only dimmable at 120V, please reference compatibility chart.

**9099X produced in 2018 and in the future are 0-10V dimming, no compatibility chart required.

Production date code can be found on the etch.



GU24 BASE

Key: DIMM = Dimmable / SL = Superior Life® / ES = Energy Star® / LM = Lumens / TRAD. EQUIV. = Traditional Equivalent

Note: For covered ceilings only. Items may not be compatible with all dimming devices. • Energy Star® items are certified at the time of production. Please visit www.energystar.gov for the most recent list of qualified products. • Published lumens on LED products are approximate and may vary slightly.



PREMIUM QUALITY LIGHTING • www.PQLighting.com

© 2018 PQL, Inc. • 2285 Ward Avenue • Simi Valley, Ca 93065 • 800.323.8107 • Fax: 877.619.7053

GO GREEN



0118