



LED MR/PAR LAMPS

The Superior Life® LED lamps are an efficient way to light sockets once reserved for traditional lamps. They consume up to 80% less energy, thereby significantly reducing operating costs. The superior life hours of this lamp make it ideal for hard to reach places, reducing maintenance.

- **ECO-FRIENDLY, MERCURY FREE**
- **NO UV**
- **PROJECTED HEAT**

Dimmable LED By incorporating advanced circuitry into our LED products, SUPERIOR LIFE® dimmable LED lamps function with switch dimmers just as normal incandescents do by allowing full linear dimming control.



V5 Lamps

ITEM#	DESCRIPTION	WATTS	DIMM	CCT	LM	LM/W	BEAM	CRI	MOL	VOLTS	BASE	LIFE	TRAD. EQUIV.	CASE
MR11/MR16														
90869	LED 3MR11/30K/35°/12V/V4 - SL°	3	NO	30K	210	70	35°	80	1.7	12	GU4	30K	20W	10/200
90935	LED 6.5MR16/30K/38°/GU5.3/12V/V4 - SL° ES°	6.5	NO	30K	500	77	38°	85	1.8	12	GU5.3	25K	50W	24
90962	LED 6.5MR16/40K/38°/GU5.3/12V/V4 - SL°	6.5	NO	40K	500	77	38°	85	1.8	12	GU5.3	40K	50W	24
90931	LED 7MR16/30K/38°/GU5.3/12V/DIMM/V4 - SL° ES°	7	YES	30K	500	71	38°	82	1.8	12	GU5.3	25K	50W	24
91784	LED 7MR16/30K/35°/GU5.3/12V/DIMM/V6 - SL° ES°	7	YES	30K	500	71	35°	80	1.9	12	GU5.3	25K	50W	60
91785	LED 7MR16/50K/35°/GU5.3/12V/DIMM/V6 - SL° ES°	7	YES	50K	500	71	35°	80	1.9	12	GU5.3	25K	50W	60
PAR16														
91787	LED 5.5PAR16/30K/40°/GU10/120V/DIMM/V6 - SL° ES°	5.5	YES	30K	400	73	40°	94	2.1	120	GU10	25K	50W	60
91780	LED 6.5PAR16/30K/40°/DIMMABLE/V6 - SL° ES°	6.5	YES	30K	500	77	40°	84	2.9	120	MEDIUM	15K	50W	60
91360	LED 6.5PAR16/30K/40°/GU10/120V/DIMM/V5 - SL° ES°	6.5	YES	30K	500	81	40°	83	2.2	120	GU10	25K	60W	48
90934	LED 7.5PAR16/30K/40°/120V/DIMM/V4 - SL° ES°	7.5	YES	30K	500	67	40°	84	2.9	120	MEDIUM	25K	75W	10/60
PAR20														
91362	LED 7PAR20/30K/25°/DIMMABLE/V5 - SL°	7	YES	30K	520	74	25°	80	3.4	120	MEDIUM	10K	50W	48
91734	LED 8PAR20/27K/25°/DIMMABLE/V6 - SL° ES°	8	YES	27K	488	61	25°	91	3.4	120	MEDIUM	15K	50W	48
90937	LED 8PAR20/30K/25°/DIMMABLE/V4 - SL°	8	YES	30K	500	63	25°	83	3.4	120	MEDIUM	25K	50W	20
91735	LED 8PAR20/30K/25°/DIMMABLE/V6 - SL° ES°	8	YES	30K	500	63	25°	91	3.4	120	MEDIUM	15K	50W	48
91736	LED 8PAR20/40K/25°/DIMMABLE/V6 - SL° ES°	8	YES	40K	500	63	25°	94	3.4	120	MEDIUM	15K	50W	48
91366	LED 8.5PAR20/50K/25°/DIMMABLE/V5 - SL° ES°	8.5	YES	50K	520	61	25°	94	3.4	120	MEDIUM	25K	50W	48

Key: DIMM = Dimmable / SL = Superior Life® / ES = Energy Star® / LM = Lumens / TRAD. EQUIV. = Traditional Equivalent

NOTE: Due to multiple input voltage integrated circuits, some items may not be compatible with dimming devices. These items may not be compatible with all electronic transformers. • Energy Star® items are certified at the time of production. Please visit www.energystar.gov for the most recent list of qualified products. • Published lumens on LED products are approximate and may vary slightly.



PREMIUM QUALITY LIGHTING® • www.PQLighting.com

© 2018 P.Q.L., Inc. • 2285 Ward Avenue • Simi Valley, Ca 93065 • 800.323.8107 • Fax: 877.619.7053



GO GREEN





V4 Lamps

ITEM#	DESCRIPTION	WATTS	DIMM	CCT	LM	LM/W	BEAM	CRI	MOL	VOLTS	BASE	LIFE	TRAD. EQUIV.	CASE
PAR30/SN														
91741	LED 12PAR30/SN/50K/25°/DIMMABLE/V6 - SL° ES°	12	YES	50K	800	67	25°	87	3.3	120	MEDIUM	15K	75W	24
91367	LED 13PAR30/SN/27K/25°/DIMMABLE/V5 - SL° ES°	13	YES	27K	800	62	25°	92	3.5	120	MEDIUM	25K	75W	24
91368	LED 13PAR30/SN/30K/25°/DIMMABLE/V5 - SL° ES°	13	YES	30K	800	62	25°	92	3.5	120	MEDIUM	25K	75W	24
91369	LED 13PAR30/SN/40K/25°/DIMMABLE/V5 - SL° ES°	13	YES	40K	800	62	25°	92	3.5	120	MEDIUM	25K	75W	24
91370	LED 13PAR30/SN/50K/25°/DIMMABLE/V5 - SL° ES°	13	YES	50K	800	62	25°	95	3.5	120	MEDIUM	25K	75W	24
PAR30/LN														
91392	LED 11PAR30/LN/27K/40°/BLACK/DIMM/V5 - SL° ES°	11	YES	27K	800	62	40°	91	4.6	120	MEDIUM	25K	75W	24
91745	LED 12PAR30/LN/27K/25°/DIMMABLE /V6 - SL° ES°	12	YES	27K	800	67	25°	92	4.3	120	MEDIUM	15K	75W	24
91746	LED 12PAR30/LN/30K/25°/DIMMABLE/V6 - SL° ES°	12	YES	30K	800	67	25°	95	4.3	120	MEDIUM	15K	75W	24
91748	LED 12PAR30/LN/50K/25°/DIMMABLE/V6 - SL° ES°	12	YES	50K	800	67	25°	96	4.3	120	MEDIUM	15K	75W	24
90956	LED 13PAR30/LN/27K/40°/DIMMABLE/V4 - SL°	13	YES	27K	800	63	40°	83	4.6	120	MEDIUM	25K	60W	20
90947	LED 13PAR30/LN/40K/25°/DIMMABLE/V4 - SL°	13	YES	40K	800	63	25°	83	4.6	120	MEDIUM	25K	60W	20
91373	LED 13PAR30/LN/40K/25°/DIMMABLE/V5 - SL° ES°	13	YES	40K	800	62	25°	94	4.6	120	MEDIUM	25K	75W	24
91374	LED 13PAR30/LN/50K/25°/DIMMABLE/V5 - SL° ES°	13	YES	50K	800	63	25°	95	4.6	120	MEDIUM	25K	75W	24
91480	LED 25PAR30/LN/25°/40K/V6 - SL°	25	NO	40K	2500	100	25°	80	4.7	120-277	MEDIUM	25K	75	12
PAR38														
91379	LED 13PAR38/30K/40°/V5 - SL°	13	NO	30K	1000	77	40°	80	5.1	120	MEDIUM	25K	120W	24
91767	LED 17PAR38/30K/40°/DIMMABLE/V6 - SL° ES°	17	YES	30K	1200	71	40°	95	4.8	120	MEDIUM	15K	120W	24
91754	LED 17PAR38/40K/25°/DIMMABLE/V6 - SL° ES°	17	YES	40K	1200	71	25°	95	4.8	120	MEDIUM	15K	120W	24
91755	LED 17PAR38/50K/25°/DIMMABLE/V6 - SL° ES°	17	YES	50K	1200	71	25°	96	4.8	120	MEDIUM	15K	120W	24
91758	LED 17PAR38/30K/25°/120-277V/V6 - SL°	17	NO	30K	1200	71	25°	90	4.8	120-277	MEDIUM	40K	120W	24
91380	LED 19PAR38/27K/25°/DIMMABLE/V5 - SL° ES°	19	YES	27K	1200	63	25°	92	5.1	120	MEDIUM	25K	120W	24
91381	LED 19PAR38/30K/25°/DIMMABLE/V5 - SL° ES°	19	YES	30K	1200	63	25°	92	5.1	120	MEDIUM	25K	120W	24
91385	LED 19PAR38/30K/40°/DIMMABLE/V5 - SL° ES°	19	YES	30K	1200	63	40°	92	5.1	120	MEDIUM	25K	120W	24
91382	LED 19PAR38/40K/25°/DIMMABLE/V5 - SL° ES°	19	YES	40K	1200	63	25°	92	5.1	120	MEDIUM	25K	120W	24
90775	LED 15PAR38/FL/50K/38°/AC100-277V - SL°	15	NO	50K	1500	100	38°	80	5.0	100-277	MEDIUM	50K	120W	50



91392



90775

Key: DIMM = Dimmable / SL = Superior Life® / ES = Energy Star® / LM = Lumens / TRAD. EQUIV. = Traditional Equivalent

NOTE: Due to multiple input voltage integrated circuits, some items may not be compatible with dimming devices. These items may not be compatible with all electronic transformers. - Energy Star® items are certified at the time of production. Please visit www.energystar.gov for the most recent list of qualified products. - Published lumens on LED products are approximate and may vary slightly.



PREMIUM QUALITY LIGHTING® • www.PQLighting.com

© 2018 P.Q.L., Inc. • 2285 Ward Avenue • Simi Valley, Ca 93065 • 800.323.8107 • Fax: 877.619.7053

