



## LIGHTING CONTROL **SENSORS**

Sensors are an efficient way to save energy without making major changes. Combining a sensor with a compatible fixture provides the ability to fine tune when the light turns on and then off after a certain amount of time. This can conserve energy and may extend the life of the fixture.

**Application:** Designed for use with fixtures in warehouses, work stations, hallways, offices or outdoor locations.

## FEATURES

- Superior performance
- Improves energy efficiency
- Lightweight and easy installation



54896



54892



54893



54890



54884 / 54885



54878



54897



54898



54888



54871



54872



54880



54895

*Note: Warranty and Qualifications can vary per item, see technical data sheets (TDS) for specific information. • Specifications are subject to change without notice. • Photos and drawings may not be to scale and are for general reference only.*



# LIGHTING CONTROL SENSORS



## PASSIVE INFRARED (PIR) SENSORS

Check TDS to confirm compatibility.

ITEM#	DESCRIPTION	VOLTS	CASE
54896	360° LOW/HIGH BAY FIXTURE OCCUPANCY PIR SENSOR 30' DIA, 8-40' HEIGHT 800W/1200W • 120/277V	120/277V	50
54892	360° OUTDOOR FIXTURE BI-LEVEL & DAYLIGHT HARVEST PIR SENSOR 30' DIA, UP TO 40' HEIGHT 800W/1200W • 120-277V	120-277V	100
54890	360° OUTDOOR FIXTURE BI-LEVEL & DAYLIGHT HARVEST PIR SENSOR 60'DIA, UP TO 40' HEIGHT 800W/1200W • 120/277V/DROP NIPPLE MOUNT	120/277V	100
54893	360° OUTDOOR FIXTURE BI-LEVEL & DAYLIGHT HARVEST PIR SENSOR 26' DIA, UP TO 40' HEIGHT 800W/1200W • 100-480V	100-480V	50
54884	LOW/HIGH BAY FIXTURE OCCUPANCY PIR SENSOR IP65 56' DIA, 8-40FT HEIGHT 800W/1200W • 120-480V	120-480V	50
54885	LOW/HIGH BAY BI-LEVEL PIR SENSOR 56' DIA, 8-40FT HEIGHT 800W/1200W • 120-480V	120-480V	50
54878	PIR MOTION ACTIVATED WALL SWITCH/3 WAY/OCC-VACANCY SINGLE POLE FOR LED/CFL/INCANDESCENT WITH WALL PLATE/WHITE	120-277V	50

## MICROWAVE SENSORS *(Dry Locations)*

ITEM#	DESCRIPTION	VOLTS	CASE
54897	360° LOW BAY BI-LEVEL AND DAYLIGHT HARVEST MICROWAVE SENSOR 48' DIA, 8-20' HEIGHT 800W/1200W • 120/277V	120/277V	50
54898	360° HIGH BAY BI-LEVEL AND DAYLIGHT HARVEST MICROWAVE SENSOR 60' DIA, 8-50' HEIGHT 800W/1200W • 120/277V	120/277V	50
54888	360° BI-LEVEL AND DAYLIGHT HARVESTING MICROWAVE SENSOR 26' DIA, 8-40' HEIGHT 800W/1200W • 120/277V	120/277V	100

## ISO SENSORS *(Requires Integrated Sensor Option)*

ITEM#	DESCRIPTION	VOLTS	CASE
54871	BI-LEVEL PIR MOTION & DAYLIGHT SCREW-IN SENSOR FOR ISO STRIPS & VAPOR TIGHTS/40FT <i>(Requires 12-24VDC AUX &amp; Elbow #54876)</i>	12-24VDC	100
54872	BI-LEVEL MICROWAVE MOTION & DAYLIGHT SCREW-IN SENSOR FOR ISO STRIPS & VAPOR TIGHTS/40FT <i>(Requires 12-24VDC AUX &amp; Elbow #54876)</i>	12-24VDC	100
54880	BI-LEVEL AND DAYLIGHT PIR SENSOR FOR ISO LED PANEL/UP TO 12FT HEIGHT • 12-24VDC	12-24VDC	100
54895	PIR DAYLIGHT HARVESTING MICROWAVE SENSOR FOR ISO TROFFER/10-14VDC <i>(Requires Adaptor #54886)</i>	10-14VDC	200

## ACCESSORIES

ITEM#	DESCRIPTION	CASE
54894	EXTENDER MOUNT FOR SENSOR 54896/54897/54898	100
54890-L4	LENS ONLY TO MAKE 54890 A LOW BAY SENSOR 60FT DIA, UP TO 20FT HEIGHT	250
54876	EXTERNAL SWIVEL QUICK CONNECT ADJUSTABLE ELBOW FOR ISO SENSORS • 54871/54872	100
54886	ADAPTER FOR 54895 ISO SENSOR FOR CENTER BASKET TROFFER	100
RC-100	HAND HELD REMOTE FOR CONFIGURING PROGRAMMABLE SENSORS	1



54894



54890-L4



54876



54886



RC-100

**Note:** Warranty and Qualifications can vary per item, see technical data sheets (TDS) for specific information. • Specifications are subject to change without notice. • Photos and drawings may not be to scale and are for general reference only.



**PREMIUM QUALITY LIGHTING® • Phone: 800-323-8107**  
© P.Q.L., Inc. • 2285 Ward Avenue • Simi Valley, CA 93065

**www.PQLighting.com**  
Rev: 02/02/2024