



Item#: 90567
LED DIRECT WIRE LINEAR T8
INTERNAL DRIVER LAMP-STYLE RETROFIT KITS
(UL TYPE B)

# **FEATURES**

Our T8 LED tube lamp provides exceptional LED lighting with reduced energy and maintenance costs. The linear LED does not use a fluorescent ballast to work; instead they feature a built-in universal line voltage driver, making it a top of the line replacement for standard fluorescent lamps.

# **SINGLE ENDED DIRECT WIRE**

- · No ballast required, lamp runs off main
- Exceptional efficacy
- \*Non-shunted sockets required, see install instructions for further details.

#### **ELECTRICAL**

Wattage	12W		
Voltage	120-277V		
Current	160-80mA		
Power Factor	0.9		
Total Harmonic Distortion (THD)	20		
LIGHTING PERFORMANCE			
Lumens	1800		

Lumens	1800
Lumens Per Watt (LPW)	150
Color Temperature (CCT)	4000K
Color Rendering (CRI)	82
R9 (Red Value)	18
R13 (Skin Tones)	86
Beam Angle	210°
Light Distribution	Type VS
Dimmable Lighting Control	See Install Instructions

# **ENVIRONMENT**

Operating Temperature	-13° ~ 113°F
Suitable Location	DAMP
Ingress Protection Rating	IP20
Suitable Fixture Type	Enclosed

#### LIFESPAN

Average Life (Hours)	50,000
Warranty (Years)	5

### **COMPONENTS**

LED LIGHT Source	Everlight 67-215

# CONSTRUCTION

Housing	Glass / Plastic End Caps Frosted	
Lens		
Base / Power Supply	G13 - Medium Bi Pin	

# **QUALIFICATIONS**









Visit www.designlights.org/search to confirm qualification. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice.


# Item#: 90567 LED DIRECT WIRE LINEAR T8



#### **DIMENSIONS** (Inches)

Length (MOL)	48"	
Width/Diameter (MOD)	1"	
Net Weight (Lbs)		

# SUPPORTING DOCUMENTS (Grey = not available at this time.) Product Sheet VIEW Install Instructions VIEW IES Download from Web Item VIEW LM79 VIEW LM80 VIEW



PACKAGING		UPC	<b>DIMENSIONS</b> (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	25	10811768025771	49.2" x 5.5" x 5.5"	14.4
Individual Box	1	811768025774		0.6
Country of Origin	China			
HS Tariff	8539.50,0050			

#### **ORDERING**

ITEM#	DESCRIPTION	CASE
90567	LED 4FT 12WT8/40K/TYPE B/SE - <b>CEE/DLC</b> °	25
ACCESSORIES		
90405	LED 5W/90MIN. EMERGENCY BATTERY BACKUP FOR (1) T8 DIRECT WIRE LAMP 120/277V - <b>T20C</b>	25

# **ADDITIONAL INFORMATION:**

# Family Item(s): 90568/5000K

• PQL Direct-Wire (UL Type B) Lamps are designed for use with PQL LED-Ready fixtures (follow lamp wiring instructions). When using any alternate-brand fixture, please review the specific PQL lamp installation guide wiring requirements first, to make sure the fixture is compatible before lamp installation.