



HALOGEN PAR

Superior Life® Enviro-Lume™ Halogen lamps are engineered with the latest technology in filament design to deliver the longest lasting halogen par on the market. PARs are ideal for retail and merchandise displays, accenting lighting, lobbies and offices.

- UP to 40% LONGER LIFE
- OPTIMIZED LUMEN OUTPUT
- UNIFORM BEAM WITHOUT HOT SPOTS
- DIMMABLE

Enviro-Lume IR™

Superior Life® Enviro-Lume IR™ Halogen lamps use the latest infrared heat technology which allows the lamp to burn cooler, generating less heat and last longer than a standard halogen. This allows for maximum efficiency, added energy savings and quality light output.



Infrared Technology

ITEM#	DESCRIPTION	BULB	WATTS	COLOR	LUMENS	LM/W	VOLT	BASE	HOURS	CASE	STD HALOGEN EQUIVALENT
96041	53PAR30/FLOOD - ENVIRO-LUME IR™	PAR30	53	FLOOD	1020	19.2	120	MEDIUM	4000	15	75
96049	53PAR30/FLOOD/LN - ENVIRO-LUME IR™	PAR30/LN	53	FLOOD	1000	18.9	120	MEDIUM	4000	15	75
96053	53PAR30/SPOT/LN - ENVIRO-LUME IR™	PAR30/LN	53	SPOT	1000	18.9	120	MEDIUM	4000	15	75

Enviro-Lume™

Superior Life® Enviro-Lume™ Halogen are an energy efficient alternative to the standard halogen.



Energy Efficient Alternative

ITEM#	DESCRIPTION	BULB	WATTS	COLOR	LUMENS	LM/W	VOLT	BASE	HOURS	CASE	STD HALOGEN EQUIVALENT
92009	38PAR20/FLOOD - ENVIRO-LUME™	PAR20	38	FLOOD	500	13.2	120	MEDIUM	1500	15	50
92017	38PAR30/FLOOD - ENVIRO-LUME™	PAR30	38	FLOOD	530	13.9	120	MEDIUM	1500	15	50
92041	60PAR30/FLOOD - ENVIRO-LUME™	PAR30	60	FLOOD	1070	17.8	120	MEDIUM	1500	15	75
92025	38PAR30/FLOOD/LN - ENVIRO-LUME™	PAR30/LN	38	FLOOD	520	13.7	120	MEDIUM	1500	15	50
92049	60PAR30/FLOOD/LN - ENVIRO-LUME™	PAR30/LN	60	FLOOD	1070	17.8	120	MEDIUM	1500	15	75
92001	38PAR38/FLOOD - ENVIRO-LUME™	PAR38	38	FLOOD	550	14.5	120	MEDIUM	1500	15	50
92057	70PAR38/FLOOD - ENVIRO-LUME™	PAR38	70	FLOOD	1310	18.7	120	MEDIUM	1500	15	90

E EISA COMPLIANT - Meets United States Minimum Efficiency Standards. Highly Efficient.



PREMIUM QUALITY LIGHTING® • www.PQLighting.com

© 2018 P.Q.L., Inc. • 2285 Ward Avenue • Simi Valley, Ca 93065 • 800.323.8107 • Fax: 877.619.7053

